

aruba config.txt

```
version 6.1.2.0-2.0.0
virtual-controller-country ID
virtual-controller-key 43e3116e01c417ed7305216f333ee5a3fa7bb1635674348c6f
name Instant-C8:81:AE
virtual-controller-ip 10.2.0.64
clock timezone Jakarta 07 00
rf-band all
```

```
allow-new-aps
allowed-ap d8:c7:c8:c8:81:ae
allowed-ap d8:c7:c8:c8:81:7c
```

```
arm
wide-bands 5ghz
min-tx-power 18
max-tx-power 127
band-steering-mode prefer-5ghz
air-time-fairness-mode fair-access
client-aware
scanning
```

```
syslog-level warn ap-debug
syslog-level warn network
syslog-level warn security
syslog-level warn system
syslog-level warn user
syslog-level warn user-debug
syslog-level warn wireless
```

```
mgmt-user admin 584875a47fbd2d14e0bb905022baf322
```

```
wlan ssid-profile barcode
index 1
type employee
ssid barcode
wpa-passphrase 164986ed543eaceeb96595ecba0ed744fa2f6bb5057d6d56
opmode wpa2-psk-aes
rf-band all
captive-portal disable
dtim-period 1
inactivity-timeout 1000
broadcast-filter none
```

```
enet-vlan guest
```

```
wlan access-rule barcode
index 1
rule any any match any any any permit
```

```
wlan external-captive-portal
server localhost
port 80
url "/"
auth-text "Authenticated"
```

```
ids classification
```

```
ids
wireless-containment none
```