

Time	Event	Description
Jan 26 10:16:34	auth	"VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10 derivation_type Default VLAN index 31.
Jan 26 10:16:34	auth	"VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0 derivation_type Current VLAN updated.
Jan 26 10:16:34	auth	"VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10 derivation_type Current VLAN updated index 0.
Jan 26 10:16:34	auth	Role Derivation for user N/A-fc:db:b3:74:f5:46- N/A Set AAA profile defaults.
Jan 26 10:16:34	auth	Idle timeout should be driven by STM for MAC fc:db:b3:74:f5:46.
Jan 26 10:16:34	auth	clr_pmcache_ft():1016: MAC:fc:db:b3:74:f5:46 BSS:18:64:72:09:4f:70
Jan 26 10:16:34	auth	Auth GSM : MAC_USER publish for mac fc:db:b3:74:f5:46 bssid 18:64:72:09:4f:70 vlan 10 type 1 data-ready 0
Jan 26 10:16:34	auth	VDR - mac fc:db:b3:74:f5:46 rolename public-access fwdmode 0 derivation_type Initial Role Contained vp not present.
Jan 26 10:16:34	auth	"VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0 derivation_type Initial Role Contained.
Jan 26 10:16:34	auth	"VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10 derivation_type Initial Role Contained index 1.

```

Jan 26 10:16:34 au th VDR - mac fc:db:b3:74:f5:46 derivation_type Initial Role Contained
m derived vlan 10.
gr

Jan 26 10:16:34 au th handle_sta_up_dn (2989): rtts user=fc:db:b3:74:f5:46 enabled=0
m initial tput=202666
gr

Jan 26 10:16:34 au th dot1x_suppllicant_up(): MAC:fc:db:b3:74:f5:46, pmkid_present:False,
m pmkid:N/A
gr

Jan 26 10:16:34 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
m derivation_type Current VLAN updated.
gr

Jan 26 10:16:34 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Current VLAN updated index 2.
gr

Jan 26 10:16:34 au th "VDR - Cur VLAN updated fc:db:b3:74:f5:46 mob 0 inform 1 remote 0
m wired 0 defvlan 10 exportedvlan 0 curvlan 10.
gr

Jan 26 10:16:34 au th MAC=fc:db:b3:74:f5:46 Station Updated Update MMS:
m BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-
gr name=Shenck_110:c8:94:f6

Jan 26 10:16:34 au th Auth GSM : USER publish for uuid 0x9ace01b7808fb066 mac
m fc:db:b3:74:f5:46 name role public-access devtype Android wired 0
gr authtype 0 subtype 0 encrypt-type 0 conn-port 8448 fwd-mode 0

Jan 26 10:16:38 st Disassoc from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
m 70-Shenck_110:c8:94:f6 Reason STA has left and is disassociated
gr

Jan 26 10:16:38 au th Auth GSM : USER_STA delete event for user fc:db:b3:74:f5:46 age 0
m deauth_reason 8
gr

Jan 26 10:16:38 st m Station fc:db:b3:74:f5:46: Clearing state

```

Jan 26 10:16:38	auth	MAC=fc:db:b3:74:f5:46 Station DN: BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
Jan 26 10:16:38	auth	Setting idle timer for user fc:db:b3:74:f5:46 to 3600 seconds (idle timeout: 3600 ageout: 0).
Jan 26 10:16:38	station	Station fc:db:b3:74:f5:46: Clearing state
Jan 26 10:16:38	station	Deauth from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6 Reason Class 2 frames from non authenticated STA
Jan 26 10:16:38	station	Station fc:db:b3:74:f5:46: No authentication found trying to de-authenticate to BSSID 18:64:72:09:4f:70 on AP Shenck_110:c8:94:f6
Jan 26 10:16:38	station	Deauth from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6 Reason Class 2 frames from non authenticated STA
Jan 26 10:16:38	station	Station fc:db:b3:74:f5:46: No authentication found trying to de-authenticate to BSSID 18:64:72:09:4f:70 on AP Shenck_110:c8:94:f6
Jan 26 10:16:45	station	Auth success: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6
Jan 26 10:16:45	station	Assoc request @ 10:16:45.142776: fc:db:b3:74:f5:46 (SN 779): AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6
Jan 26 10:16:45	station	Assoc success @ 10:16:45.144650: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6
Jan 26 10:16:45	station	Assoc success @ 10:16:45.142112: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

```

Jan 26 10:16:45 au th m gr Auth GSM : USER_STA event 0 for user fc:db:b3:74:f5:46
Jan 26 10:16:45 au th m gr MAC=fc:db:b3:74:f5:46 Station UP: BSSID=18:64:72:09:4f:70
10:16:45 m gr ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
Jan 26 10:16:45 au th m gr MAC=fc:db:b3:74:f5:46 ingress 0x0x10091 (tunnel 145), u_encr 1,
10:16:45 m gr m_encr 1, slotport 0x0x2100 , type: local, FW mode: 0, AP IP: 0.0.0.0
6:45 gr mdie 0 ft_complete 0
Jan 26 10:16:45 au th m gr MAC=fc:db:b3:74:f5:46, wired: 0, vlan:10 ingress:0x0x10091 (tunnel
10:16:45 m gr 145), ingress:0x0x10091 new_aaa_prof: WIRELESS-aaa-profile, stored
6:45 gr profile: WIRELESS-aaa-profile stored wired: 0 stored essid: WIRELESS,
stored-ingress: 0x0x10091
Jan 26 10:16:45 au th m gr User idle timer removed for user with MAC fc:db:b3:74:f5:46.
Jan 26 10:16:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 0
10:16:45 m gr derivation_type Reset VLANs for Station up index 3.
Jan 26 10:16:45 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
10:16:45 m gr derivation_type Default VLAN.
Jan 26 10:16:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
10:16:45 m gr derivation_type Default VLAN index 4.
Jan 26 10:16:45 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
10:16:45 m gr derivation_type Current VLAN updated.
Jan 26 10:16:45 m dn s mdns_parse_auth_userapname_message 452 Auth->MDNS User
10:16:45 s APNAME: MAC:fc:db:b3:74:f5:46, NEW AP NAME:Shenck_110:c8:94:f6
Jan 26 10:16:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
10:16:45 m gr derivation_type Current VLAN updated index 5.

```

```
Jan 26 10:16:45 au th m gr Role Derivation for user N/A-fc:db:b3:74:f5:46- N/A Set AAA profile defaults.
Jan 26 10:16:45 au th m gr Idle timeout should be driven by STM for MAC fc:db:b3:74:f5:46.
Jan 26 10:16:45 au th m gr clr_pmkcachefc:db:b3:74:f5:46 BSS:18:64:72:09:4f:70
Jan 26 10:16:45 au th m gr Auth GSM : MAC_USER publish for mac fc:db:b3:74:f5:46 bssid 18:64:72:09:4f:70 vlan 10 type 1 data-ready 0
Jan 26 10:16:45 au th m gr VDR - mac fc:db:b3:74:f5:46 rolename public-access fwdmode 0 derivation_type Initial Role Contained vp not present.
Jan 26 10:16:45 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0 derivation_type Initial Role Contained.
Jan 26 10:16:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10 derivation_type Initial Role Contained index 6.
Jan 26 10:16:45 au th m gr VDR - mac fc:db:b3:74:f5:46 derivation_type Initial Role Contained derived vlan 10.
Jan 26 10:16:45 au th m gr handle_sta_up_dn (2989): rtts user=fc:db:b3:74:f5:46 enabled=0 initial tput=192000
Jan 26 10:16:45 au th m gr dot1x_supplifcant_up(): MAC:fc:db:b3:74:f5:46, pmkid_present:False, pmkid:N/A
Jan 26 10:16:45 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0 derivation_type Current VLAN updated.
```

```

Jan 26 10:16:45 au th "VDR - Add to history of user fc:db:b3:74:f5:46 vlan 10
m derivation_type Current VLAN updated index 7.
gr

Jan 26 10:16:45 au th "VDR - Cur VLAN updated fc:db:b3:74:f5:46 mob 0 inform 1 remote 0
m wired 0 defvlan 10 exportedvlan 0 curvlan 10.
gr

Jan 26 10:16:45 au th MAC=fc:db:b3:74:f5:46 Station Updated Update MMS:
m BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-
gr name=Shenck_110:c8:94:f6

Jan 26 10:16:45 au th Auth GSM : USER publish for uuid 0x9ace01b7808fb066 mac
m fc:db:b3:74:f5:46 name role public-access devtype Android wired 0
gr authtype 0 subtype 0 encrypt-type 0 conn-port 8448 fwd-mode 0

Jan 26 10:16:47 st Disassoc from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
m 70-Shenck_110:c8:94:f6 Reason STA has left and is disassociated
6:47

Jan 26 10:16:47 au th Auth GSM : USER_STA delete event for user fc:db:b3:74:f5:46 age 0
m deauth_reason 8
gr

Jan 26 10:16:47 au th MAC=fc:db:b3:74:f5:46 Station DN: BSSID=18:64:72:09:4f:70
m ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
gr

Jan 26 10:16:47 au th Setting idle timer for user fc:db:b3:74:f5:46 to 3600 seconds (idle
m timeout: 3600 ageout: 0).
gr

Jan 26 10:16:47 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:16:47 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:16:51 st m Auth success: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-
m Shenck_110:c8:94:f6
6:51

```

```

Jan 26 st Assoc request @ 10:16:51.498669: fc:db:b3:74:f5:46 (SN 806): AP
10:1 m 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6
6:51

Jan 26 st Assoc success @ 10:16:51.500094: fc:db:b3:74:f5:46: AP
10:1 m 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6
6:51

Jan 26 st Assoc success @ 10:16:51.496920: fc:db:b3:74:f5:46: AP
10:1 m 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6
6:51

Jan 26 au
10:1 th Auth GSM : USER_STA event 0 for user fc:db:b3:74:f5:46
6:51 m
gr

Jan 26 au
10:1 th MAC=fc:db:b3:74:f5:46 Station UP: BSSID=18:64:72:09:4f:70
6:51 m ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
gr

Jan 26 au MAC=fc:db:b3:74:f5:46 ingress 0x0x10091 (tunnel 145), u_encr 1,
10:1 th m_m_encr 1, slotport 0x0x2100 , type: local, FW mode: 0, AP IP: 0.0.0.0
6:51 m mdie 0 ft_complete 0
gr

Jan 26 au MAC=fc:db:b3:74:f5:46, wired: 0, vlan:10 ingress:0x0x10091 (tunnel
10:1 th 145), ingress:0x0x10091 new_aaa_prof: WIRELESS-aaa-profile, stored
6:51 m profile: WIRELESS-aaa-profile stored wired: 0 stored essid: WIRELESS,
gr stored-ingress: 0x0x10091

Jan 26 au
10:1 th User idle timer removed for user with MAC fc:db:b3:74:f5:46.
6:51 m
gr

Jan 26 au
10:1 th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 0
6:51 m derivation_type Reset VLANs for Station up index 8.
gr

Jan 26 au
10:1 th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
6:51 m derivation_type Default VLAN.
gr

Jan 26 au
10:1 th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
6:51 m derivation_type Default VLAN index 9.
gr

```

```

Jan 26 10:16:51 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
m derivation_type Current VLAN updated.
gr

Jan 26 10:16:51 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Current VLAN updated index 10.
gr

Jan 26 10:16:51 au th Role Derivation for user N/A-fc:db:b3:74:f5:46- N/A Set AAA profile
m defaults.
gr

Jan 26 10:16:51 au th Idle timeout should be driven by STM for MAC fc:db:b3:74:f5:46.
m
gr

Jan 26 10:16:51 m dn mdns_parse_auth_userapname_message 452 Auth->MDNS User
s APNAME: MAC:fc:db:b3:74:f5:46, NEW AP NAME:Shenck_110:c8:94:f6

Jan 26 10:16:51 au th clr_pmkcachef():1016: MAC:fc:db:b3:74:f5:46 BSS:18:64:72:09:4f:
m 70
gr

Jan 26 10:16:51 au th Auth GSM : MAC_USER publish for mac fc:db:b3:74:f5:46 bssid
m 18:64:72:09:4f:70 vlan 10 type 1 data-ready 0
gr

Jan 26 10:16:51 au th VDR - mac fc:db:b3:74:f5:46 rolename public-access fwdmode 0
m derivation_type Initial Role Contained vp not present.
gr

Jan 26 10:16:51 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
m derivation_type Initial Role Contained.
gr

Jan 26 10:16:51 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Initial Role Contained index 11.
gr

Jan 26 10:16:51 au th VDR - mac fc:db:b3:74:f5:46 derivation_type Initial Role Contained
m derived vlan 10.
gr

```



```

Jan 26 10:16:51 au th handle_sta_up_dn (2989): rtts user=fc:db:b3:74:f5:46 enabled=0
m initial tput=197333
gr

Jan 26 10:16:51 au th dot1x_suppllicant_up(): MAC:fc:db:b3:74:f5:46, pmkid_present:False,
m pmkid:N/A
gr

Jan 26 10:16:51 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
m derivation_type Current VLAN updated.
gr

Jan 26 10:16:51 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Current VLAN updated index 12.
gr

Jan 26 10:16:51 au th "VDR - Cur VLAN updated fc:db:b3:74:f5:46 mob 0 inform 1 remote 0
m wired 0 defvlan 10 exportedvlan 0 curvlan 10.
gr

Jan 26 10:16:51 au th MAC=fc:db:b3:74:f5:46 Station Updated Update MMS:
m BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-
gr name=Shenck_110:c8:94:f6

Jan 26 10:16:51 au th Auth GSM : USER publish for uuid 0x9ace01b7808fb066 mac
m fc:db:b3:74:f5:46 name role public-access devtype Android wired 0
gr authtype 0 subtype 0 encrypt-type 0 conn-port 8448 fwd-mode 0

Jan 26 10:16:53 st Disassoc from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
m 70-Shenck_110:c8:94:f6 Reason STA has left and is disassociated

Jan 26 10:16:53 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:16:53 st m Deauth from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
m 70-Shenck_110:c8:94:f6 Reason Class 2 frames from non authenticated
STA

Jan 26 10:16:53 au th Auth GSM : USER_STA delete event for user fc:db:b3:74:f5:46 age 0
m deauth_reason 8
gr

```

```

Jan 26 10:16:53 st m Station fc:db:b3:74:f5:46: No authentication found trying to de-
authenticate to BSSID 18:64:72:09:4f:70 on AP Shenck_110:c8:94:f6

Jan 26 10:16:53 au th MAC=fc:db:b3:74:f5:46 Station DN: BSSID=18:64:72:09:4f:70
m ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
gr

Jan 26 10:16:53 au th Setting idle timer for user fc:db:b3:74:f5:46 to 3600 seconds (idle
m timeout: 3600 ageout: 0).
gr

Jan 26 10:16:53 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:17:00 st m Auth success: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-
Shenck_110:c8:94:f6

Jan 26 10:17:00 st m Assoc request @ 10:17:00.994907: fc:db:b3:74:f5:46 (SN 835): AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:17:00 st m Assoc success @ 10:17:00.996325: fc:db:b3:74:f5:46: AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:17:00 st m Assoc success @ 10:17:00.993252: fc:db:b3:74:f5:46: AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:17:00 au th m Auth GSM : USER_STA event 0 for user fc:db:b3:74:f5:46
gr

Jan 26 10:17:00 au th MAC=fc:db:b3:74:f5:46 Station UP: BSSID=18:64:72:09:4f:70
m ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
gr

Jan 26 10:17:00 au th MAC=fc:db:b3:74:f5:46 ingress 0x0x10091 (tunnel 145), u_encr 1,
m m_encr 1, slotport 0x0x2100 , type: local, FW mode: 0, AP IP: 0.0.0.0
gr mdie 0 ft_complete 0

```

```

Jan 26 10:17:00 au th MAC=fc:db:b3:74:f5:46, wired: 0, vlan:10 ingress:0x0x10091 (tunnel
145), ingress:0x0x10091 new_aaa_prof: WIRELESS-aaa-profile, stored
10:1 m profile: WIRELESS-aaa-profile stored wired: 0 stored essid: WIRELESS,
7:00 gr stored-ingress: 0x0x10091

Jan 26 10:17:00 au th User idle timer removed for user with MAC fc:db:b3:74:f5:46.
10:1 m
7:00 gr

Jan 26 10:17:00 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 0
10:1 m derivation_type Reset VLANs for Station up index 13.
7:00 gr

Jan 26 10:17:00 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
10:1 m derivation_type Default VLAN.
7:00 gr

Jan 26 10:17:00 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
10:1 m derivation_type Default VLAN index 14.
7:00 gr

Jan 26 10:17:00 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
10:1 m derivation_type Current VLAN updated.
7:00 gr

Jan 26 10:17:00 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
10:1 m derivation_type Current VLAN updated index 15.
7:00 gr

Jan 26 10:17:00 m dn mdns_parse_auth_userapname_message 452 Auth->MDNS User
10:1 s APNAME: MAC:fc:db:b3:74:f5:46, NEW AP NAME:Shenck_110:c8:94:f6
7:00

Jan 26 10:17:00 au th Role Derivation for user N/A-fc:db:b3:74:f5:46- N/A Set AAA profile
10:1 m defaults.
7:00 gr

Jan 26 10:17:00 au th Idle timeout should be driven by STM for MAC fc:db:b3:74:f5:46.
10:1 m
7:00 gr

Jan 26 10:17:00 au th clr_pmocache_ft():1016: MAC:fc:db:b3:74:f5:46 BSS:18:64:72:09:4f:
10:1 m 70
7:00 gr

```

```
Jan 26 10:17:00 au th Auth GSM : MAC_USER publish for mac fc:db:b3:74:f5:46 bssid  
18:64:72:09:4f:70 vlan 10 type 1 data-ready 0  
gr  
Jan 26 10:17:00 au th VDR - mac fc:db:b3:74:f5:46 rolename public-access fwdmode 0  
m derivation_type Initial Role Contained vp not present.  
gr  
Jan 26 10:17:00 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0  
m derivation_type Initial Role Contained.  
gr  
Jan 26 10:17:00 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10  
m derivation_type Initial Role Contained index 16.  
gr  
Jan 26 10:17:00 au th VDR - mac fc:db:b3:74:f5:46 derivation_type Initial Role Contained  
m derived vlan 10.  
gr  
Jan 26 10:17:00 au th handle_sta_up_dn (2989): rtts user=fc:db:b3:74:f5:46 enabled=0  
m initial tput=202666  
gr  
Jan 26 10:17:00 au th dot1x_suppllicant_up(): MAC:fc:db:b3:74:f5:46, pmkid_present:False,  
m pmkid:N/A  
gr  
Jan 26 10:17:00 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0  
m derivation_type Current VLAN updated.  
gr  
Jan 26 10:17:00 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10  
m derivation_type Current VLAN updated index 17.  
gr  
Jan 26 10:17:00 au th "VDR - Cur VLAN updated fc:db:b3:74:f5:46 mob 0 inform 1 remote 0  
m wired 0 defvlan 10 exportedvlan 0 curvlan 10.  
gr  
Jan 26 10:17:00 au th MAC=fc:db:b3:74:f5:46 Station Updated Update MMS:  
m BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-  
name=Shenck_110:c8:94:f6  
gr
```

```

Jan 26 10:17:00 au th m gr Auth GSM : USER publish for uuid 0x9ace01b7808fb066 mac
fc:db:b3:74:f5:46 name role public-access devtype Android wired 0
authtype 0 subtype 0 encrypt-type 0 conn-port 8448 fwd-mode 0

Jan 26 10:17:03 au th m gr Auth GSM : USER_STA delete event for user fc:db:b3:74:f5:46 age 0
death_reason 8

Jan 26 10:17:03 st m Disassoc from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
70-Shenck_110:c8:94:f6 Reason STA has left and is disassociated

Jan 26 10:17:03 au th m gr MAC=fc:db:b3:74:f5:46 Station DN: BSSID=18:64:72:09:4f:70
ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6

Jan 26 10:17:03 au th m gr Setting idle timer for user fc:db:b3:74:f5:46 to 3600 seconds (idle
timeout: 3600 ageout: 0).

Jan 26 10:17:03 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:17:03 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:17:08 st m Auth success: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-
Shenck_110:c8:94:f6

Jan 26 10:17:08 st m Assoc request @ 10:17:08.660591: fc:db:b3:74:f5:46 (SN 901): AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:17:08 st m Assoc success @ 10:17:08.658890: fc:db:b3:74:f5:46: AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:17:08 st m Assoc success @ 10:17:08.662209: fc:db:b3:74:f5:46: AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

```

```

Jan 26 10:17:08 au th m gr Auth GSM : USER_STA event 0 for user fc:db:b3:74:f5:46
Jan 26 10:17:08 au th m gr MAC=fc:db:b3:74:f5:46 Station UP: BSSID=18:64:72:09:4f:70
10:17:08 m gr ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
Jan 26 10:17:08 au th m gr MAC=fc:db:b3:74:f5:46 ingress 0x0x10091 (tunnel 145), u_encr 1,
10:17:08 m gr m_encr 1, slotport 0x0x2100 , type: local, FW mode: 0, AP IP: 0.0.0.0
7:08 mdie 0 ft_complete 0
Jan 26 10:17:08 au th m gr MAC=fc:db:b3:74:f5:46, wired: 0, vlan:10 ingress:0x0x10091 (tunnel
10:17:08 m gr 145), ingress:0x0x10091 new_aaa_prof: WIRELESS-aaa-profile, stored
7:08 m gr profile: WIRELESS-aaa-profile stored wired: 0 stored essid: WIRELESS,
stored-ingress: 0x0x10091
Jan 26 10:17:08 au th m gr User idle timer removed for user with MAC fc:db:b3:74:f5:46.
Jan 26 10:17:08 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 0
10:17:08 m gr derivation_type Reset VLANs for Station up index 18.
Jan 26 10:17:08 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
10:17:08 m gr derivation_type Default VLAN.
Jan 26 10:17:08 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
10:17:08 m gr derivation_type Default VLAN index 19.
Jan 26 10:17:08 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
10:17:08 m gr derivation_type Current VLAN updated.
Jan 26 10:17:08 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
10:17:08 m gr derivation_type Current VLAN updated index 20.
Jan 26 10:17:08 m dn s mdns_parse_auth_userapname_message 452 Auth->MDNS User
10:17:08 s dn s APNAME: MAC:fc:db:b3:74:f5:46, NEW AP NAME:Shenck_110:c8:94:f6

```

```
Jan 26 10:17:08 au th Role Derivation for user N/A-fc:db:b3:74:f5:46- N/A Set AAA profile defaults.
Jan 26 10:17:08 au th Idle timeout should be driven by STM for MAC fc:db:b3:74:f5:46.
Jan 26 10:17:08 au th clr_pmkcachefc:db:b3:74:f5:46 BSS:18:64:72:09:4f:70
Jan 26 10:17:08 au th Auth GSM : MAC_USER publish for mac fc:db:b3:74:f5:46 bssid 18:64:72:09:4f:70 vlan 10 type 1 data-ready 0
Jan 26 10:17:08 au th VDR - mac fc:db:b3:74:f5:46 rolename public-access fwdmode 0 derivation_type Initial Role Contained vp not present.
Jan 26 10:17:08 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0 derivation_type Initial Role Contained.
Jan 26 10:17:08 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10 derivation_type Initial Role Contained index 21.
Jan 26 10:17:08 au th VDR - mac fc:db:b3:74:f5:46 derivation_type Initial Role Contained derived vlan 10.
Jan 26 10:17:08 au th handle_sta_up_dn (2989): rtts user=fc:db:b3:74:f5:46 enabled=0 initial tput=186666
Jan 26 10:17:08 au th dot1x_supplifcant_up(): MAC:fc:db:b3:74:f5:46, pmkid_present:False, pmkid:N/A
Jan 26 10:17:08 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0 derivation_type Current VLAN updated.
```

```

Jan 26 10:17:08 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Current VLAN updated index 22.
gr

Jan 26 10:17:08 au th "VDR - Cur VLAN updated fc:db:b3:74:f5:46 mob 0 inform 1 remote 0
m wired 0 defvlan 10 exportedvlan 0 curvlan 10.
gr

Jan 26 10:17:08 au th MAC=fc:db:b3:74:f5:46 Station Updated Update MMS:
m BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-
gr name=Shenck_110:c8:94:f6

Jan 26 10:17:08 au th Auth GSM : USER publish for uuid 0x9ace01b7808fb066 mac
m fc:db:b3:74:f5:46 name role public-access devtype Android wired 0
gr authtype 0 subtype 0 encrypt-type 0 conn-port 8448 fwd-mode 0

Jan 26 10:17:09 st Disassoc from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
m 70-Shenck_110:c8:94:f6 Reason STA has left and is disassociated

Jan 26 10:17:09 au th Auth GSM : USER_STA delete event for user fc:db:b3:74:f5:46 age 0
m deauth_reason 8
gr

Jan 26 10:17:09 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:17:09 au th MAC=fc:db:b3:74:f5:46 Station DN: BSSID=18:64:72:09:4f:70
m ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
gr

Jan 26 10:17:09 au th Setting idle timer for user fc:db:b3:74:f5:46 to 3600 seconds (idle
m timeout: 3600 ageout: 0).
gr

Jan 26 10:17:09 st m Station fc:db:b3:74:f5:46: Clearing state

Jan 26 10:17:09 st m Deauth from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:
70-Shenck_110:c8:94:f6 Reason Class 2 frames from non authenticated
STA

```



```

Jan 26 10:17:09 st m Station fc:db:b3:74:f5:46: No authentication found trying to de-
authenticate to BSSID 18:64:72:09:4f:70 on AP Shenck_110:c8:94:f6

Jan 26 10:17:47 st m Deauth to sta: fc:db:b3:74:f5:46: Ageout AP
10.0.192.23-18:64:72:09:4f:60-Shenck_110:c8:94:f6 handle_sapcp

Jan 26 10:17:47 st m Deauth to sta: fc:db:b3:74:f5:46: Ageout AP
10.0.192.23-18:64:72:09:4f:60-Shenck_110:c8:94:f6 Sapcp Ageout
(internal ageout)

Jan 26 10:22:45 st m Auth success: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-
Shenck_110:c8:94:f6

Jan 26 10:22:45 st m Assoc request @ 10:22:45.758062: fc:db:b3:74:f5:46 (SN 38): AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:22:45 st m Assoc success @ 10:22:45.759864: fc:db:b3:74:f5:46: AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:22:45 st m Assoc success @ 10:22:45.761090: fc:db:b3:74:f5:46: AP
10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6

Jan 26 10:22:45 au th m gr Auth GSM : USER_STA event 0 for user fc:db:b3:74:f5:46

Jan 26 10:22:45 au th m gr MAC=fc:db:b3:74:f5:46 Station UP: BSSID=18:64:72:09:4f:70
ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6

Jan 26 10:22:45 au th m gr MAC=fc:db:b3:74:f5:46 ingress 0x0x10091 (tunnel 145), u_encr 1,
m_encr 1, slotport 0x0x2100 , type: local, FW mode: 0, AP IP: 0.0.0.0
mdie 0 ft_complete 0

Jan 26 10:22:45 au th m gr MAC=fc:db:b3:74:f5:46, wired: 0, vlan:10 ingress:0x0x10091 (tunnel
145), ingress:0x0x10091 new_aaa_prof: WIRELESS-aaa-profile, stored
profile: WIRELESS-aaa-profile stored wired: 0 stored essid: WIRELESS,
stored-ingress: 0x0x10091

```

```

Jan 26 10:22:45 au th m gr User idle timer removed for user with MAC fc:db:b3:74:f5:46.
Jan 26 10:22:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 0
derivation_type Reset VLANs for Station up index 23.
Jan 26 10:22:45 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
derivation_type Default VLAN.
Jan 26 10:22:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
derivation_type Default VLAN index 24.
Jan 26 10:22:45 au th m gr "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
derivation_type Current VLAN updated.
Jan 26 10:22:45 au th m gr "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
derivation_type Current VLAN updated index 25.
Jan 26 10:22:45 m dn s mdns_parse_auth_userapname_message 452 Auth->MDNS User
APNAME: MAC:fc:db:b3:74:f5:46, NEW AP NAME:Shenck_110:c8:94:f6
Jan 26 10:22:45 au th m gr Role Derivation for user N/A-fc:db:b3:74:f5:46- N/A Set AAA profile
defaults.
Jan 26 10:22:45 au th m gr Idle timeout should be driven by STM for MAC fc:db:b3:74:f5:46.
Jan 26 10:22:45 au th m gr clr_pmktcache_ft():1016: MAC:fc:db:b3:74:f5:46 BSS:18:64:72:09:4f:
70
Jan 26 10:22:45 au th m gr Auth GSM : MAC_USER publish for mac fc:db:b3:74:f5:46 bssid
18:64:72:09:4f:70 vlan 10 type 1 data-ready 0

```

```

Jan 26 10:22:45 au th VDR - mac fc:db:b3:74:f5:46 rolename public-access fwdmode 0
m derivation_type Initial Role Contained vp not present.
gr

Jan 26 10:22:45 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
m derivation_type Initial Role Contained.
gr

Jan 26 10:22:45 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Initial Role Contained index 26.
gr

Jan 26 10:22:45 au th VDR - mac fc:db:b3:74:f5:46 derivation_type Initial Role Contained
m derived vlan 10.
gr

Jan 26 10:22:45 au th handle_sta_up_dn (2989): rtts user=fc:db:b3:74:f5:46 enabled=0
m initial tput=176000
gr

Jan 26 10:22:45 au th dot1x_supPLICANT_up(): MAC:fc:db:b3:74:f5:46, pmkid_present:False,
m pmkid:N/A
gr

Jan 26 10:22:45 au th "VDR - set vlan in user for fc:db:b3:74:f5:46 vlan 10 fwdmode 0
m derivation_type Current VLAN updated.
gr

Jan 26 10:22:45 au th "VDR - Add to history of user user fc:db:b3:74:f5:46 vlan 10
m derivation_type Current VLAN updated index 27.
gr

Jan 26 10:22:45 au th "VDR - Cur VLAN updated fc:db:b3:74:f5:46 mob 0 inform 1 remote 0
m wired 0 defvlan 10 exportedvlan 0 curvlan 10.
gr

Jan 26 10:22:45 au th MAC=fc:db:b3:74:f5:46 Station Updated Update MMS:
m BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-
gr name=Shenck_110:c8:94:f6

Jan 26 10:22:45 au th Auth GSM : USER publish for uuid 0x9ace01b7808fb066 mac
m fc:db:b3:74:f5:46 name role public-access devtype Android wired 0
gr authtype 0 subtype 0 encrypt-type 0 conn-port 8448 fwd-mode 0

```

Jan 26 10:2 2:48	st m	Disassoc from sta: fc:db:b3:74:f5:46: AP 10.0.192.23-18:64:72:09:4f:70-Shenck_110:c8:94:f6 Reason STA has left and is disassociated
Jan 26 10:2 2:48	au th m gr	Auth GSM : USER_STA delete event for user fc:db:b3:74:f5:46 age 0 deauth_reason 8
Jan 26 10:2 2:48	st m	Station fc:db:b3:74:f5:46: Clearing state
Jan 26 10:2 2:48	au th m gr	MAC=fc:db:b3:74:f5:46 Station DN: BSSID=18:64:72:09:4f:70 ESSID=WIRELESS VLAN=10 AP-name=Shenck_110:c8:94:f6
Jan 26 10:2 2:48	au th m gr	Setting idle timer for user fc:db:b3:74:f5:46 to 3600 seconds (idle timeout: 3600 ageout: 0).
Jan 26 10:2 2:48	st m	Station fc:db:b3:74:f5:46: Clearing state