Miscellaneous Enhancements

AOS-CX 10.09

Matt Fern

Technical Marketing Engineering



Downloadable User Roles (DUR) on 4100i

Support for Downloadable User Roles (DUR) has been added to the 4100i platform as part of the Dynamic Segmentation feature set as part of the 10.09 release.

DUR configuration and functionality on the 4100i are identical to the CX 6200, 6300, and 6400.



CX 6400 RPVST scale increase

RPVST on the CX 6400 series has been enhanced in AOS-CX 10.09 to support up to 768 RPVST VLANs per system (increased from 254 in prior versions).

There is no change to the maximum number of RPVST virtual ports (2048).



Dynamic ARP Inspection for CX 6000 and 6100

The Dynamic ARP Inspection feature has been extended to the CX 6000 and 6100 platforms in the AOS-CX 10.09 release.

Feature configuration on these new platforms is unchanged from that previously supported on the CX 6200, 6300, 6400, and 8400 platforms.

DHCPv4 Snooping for 6000 and 6100

The DHCPv4 Snooping feature has been extended to the CX 6000 and 6100 platforms in the AOS-CX 10.09 release.

Feature configuration on these new platforms is unchanged from that previously supported on the CX 4100i, 6200, 6300, and 6400 platforms

Maximum number of DHCPv4 bindings per port: 256





Thank you

mfern@hpe.com