

Packet #372

ID: 372
Date received: 2012-09-19 11:27:51.597 (+0100)
Time since first packet: 70.862377 seconds
Packet length: 74 bytes
Captured length: 74 bytes

Ethernet-Header

Source: 00:0b:86:11:9c:80
Destination: b8:ac:6f:99:ba:af
Type: IP (0x0800)

IP-Header

Length: 20 bytes
Version: 4
 Differentiated Services: 0x00
 DS: 000000
 ECN: 0
 CE: 0
Total length: 60 bytes
Identification: 0x0000 (0)
 Fragment flags: 0x04
 R-Bit: 0
 DF-Bit: 1
 MF-Bit: 0
Fragment offset: 0
Time to live: 64
Protocol: UDP (0x11)
Checksum: 0x1c9d
Source: 10.1.5.9
Destination: 10.1.5.10

UDP-Header

Length: 8 bytes
Source Port: 3799 (RADIUSACCT)
Destination Port: 3799 (RADIUSACCT)
Checksum: 0x83ce
Total length: 40 bytes

RADIUS-Header

Length: 32 bytes
Code: CoA-NAK (45)
Identifier: 39 (0x27)
Authenticator: 724036CBA4495F1216E37FBE805BFF37
 AVP 4 - NAS-IP-Address
 Attribute: NAS-IP-Address (4)
 Length: 6 bytes
 Address: 10.1.5.9
 AVP 61 - NAS-Port-Type
 Attribute: NAS-Port-Type (61)
 Length: 6 bytes
 Type: Wireless - IEEE 802.11 (19)

Binary Data (Length: 74 bytes)

00000	b8 ac 6f 99 ba af 00 0b	86 11 9c 80 08 00 45 00	..O.....E.
00010	00 3c 00 00 40 00 40 11	1c 9d 0a 01 05 09 0a 01	.<..@.@.....
00020	05 0a 0e d7 0e d7 00 28	83 ce 2d 27 00 20 72 40	(..-' . r@
00030	36 cb a4 49 5f 12 16 e3	7f be 80 5b ff 37 04 06	6..I_.....[.7..
00040	0a 01 05 09 3d 06 00 00	00 13	=.....

